

Wood Click

Wood Click

WOOD CLICK is a PVC decorative tile with wood design and texture produced by high pressure impact process. Featuring with Unilin L2C patented technologies, making installation fast and simple in all possible ways. It benefits from PU polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.

Place Recommended

Housing, Healthcare, Hospital, Clinic, Office Administration, Education, Hotel, Restaurant, Retail



WC-8923

Deep Wood



WC-5214

Deep Wood



WC-3412

Deep Wood



WC-3801

Deep Wood



	Size
	Thickness
	Wear Layer
	Type
	Edges
	Treatment

178.1 X 1244.6 mm.

5.0 mm.

0.30 mm.

Plank

Bevelled

PU

Shades and colors may vary slightly from actual tiles, please request actual sample from Marketing and Sales Department

WOOD CLICK is a PVC decorative tile with wood design and texture produced by high pressure impact process. Featuring with Unilin L2C patented technologies, making installation fast and simple in all possible ways. It benefits from PU polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.



PLAYING JIGSAW!

Easy for install and replacing with a good result. With technology of PVC flooring that we never stop to explore and develop the best for you.

Installing

1. Preparing Subfloor



Hard, level, dry, smooth, sound and clean

2. Laying Method.



2.1 Unpack tiles 48hrs. before laying



2.2 Trace a line perpendicular to the main entrance. Ensure equal cut of tiles at the room perimeter.



2.3 Position the panel at an angle of 20°-30° to the panel already installed



2.4 Move the panel gently up and down and at the same time exert forward with pressure



2.5 The panels will automatically click into place

Maintenance



Remove loose debris



Low speed cleaning machine



Apply wax



Daily Maintenance

Dry sweeping or remove dirt with a damp mop



Periodic Maintenance

High speed cleaning machine

For full specification, installation, and maintenance details, please refer to the handbook

Wood Click

Wood Click

WOOD CLICK is a PVC decorative tile with wood design and texture produced by high pressure impact process. Featuring with Unilin L2C patented technologies, making installation fast and simple in all possible ways. It benefits from PU polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.

Place Recommended

Housing, Healthcare, Hospital, Clinic, Office Administration, Education, Hotel, Restaurant, Retail



	Size 178.1 X 1244.6 mm.
	Thickness 5.0 mm.
	Wear Layer 0.30 mm.
	Type Plank
	Edges Bevelled
	Treatment PU

Shades and colors may vary slightly from actual tiles, please request actual sample from Marketing and Sales Department

WC-8209

Fine

WC-1216

Rough

WC-9304

Rough

WC-2205

Saw Cut



WOOD CLICK is a PVC decorative tile with wood design and texture produced by high pressure impact process. Featuring with Unilin L2C patented technologies, making installation fast and simple in all possible ways. It benefits from PU polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.



I CLICK WITH THE IDEA

Still able to support your dream perfectly with many color. We do trust in your first click.

Installing

1. Preparing Subfloor



Hard, level, dry, smooth, sound and clean

2. Laying Method.



2.1 Unpack tiles 48hrs. before laying



2.2 Trace a line perpendicular to the main entrance. Ensure equal cut of tiles at the room perimeter.



2.3 Position the panel at an angle of 20°-30° to the panel already installed



2.4 Move the panel gently up and down and at the same time exert forward with pressure



2.5 The panels will automatically click into place

Maintenance

Initial Cleaning



Remove loose debris



Low speed cleaning machine

Protection



Apply wax

Daily Maintenance



Dry sweeping or remove dirt with a damp mop



High speed cleaning machine

For full specification, installation, and maintenance details, please refer to the handbook