

# Wood

## Wood

WOOD is flexible PVC decorative tile with wood design and texture produced by high pressure impact process. It benefits from PUR polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.

## Place Recommended

Housing, Healthcare, Hospital, Clinic, Office Administration, Education, Hotel, Restaurant, Retail



|  |                           |
|--|---------------------------|
|  | Size<br>152.4 x 914.4 mm. |
|  | Thickness<br>2.5 mm.      |
|  | Wear Layer<br>0.30 mm.    |
|  | Type<br>Plank             |
|  | Treatment<br>PUR          |

|        |            |        |            |        |            |        |            |        |            |
|--------|------------|--------|------------|--------|------------|--------|------------|--------|------------|
| WT-181 | Desire     | WT-183 | Desire     | W-939  | Desire     | W-969  | Desire     | W-1221 | Desire     |
|        |            |        |            |        |            |        |            |        |            |
| W-8112 | NEW Desire | W-0124 | NEW Desire | W-5311 | NEW Desire | W-5317 | NEW Desire | W-7417 | NEW Desire |
|        |            |        |            |        |            |        |            |        |            |

WOOD is flexible PVC decorative tile with wood design and texture produced by high pressure impact process. It benefits from PUR polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.



### FEELING WARM

We provide the emotion that never happened before.

## Installing

### 1. Preparing Subfloor



Hard, level, dry, smooth, sound and clean

### 2. Laying Method



2.1 Unpack tiles 24 hrs. before laying



2.2 Trace a line perpendicular to the main entrance. Ensure equal cut of tiles at the room perimeter.



2.3 Apply adhesive to a few sq.m of subfloor in one quarter



2.4 Press each tile into position



2.5 Roll with 50kg roller

## Maintenance



Remove loose debris



Initial Cleaning  
Low speed cleaning machine



Apply wax



Daily Maintenance

Dry sweeping or remove dirt with a damp mop



Periodic Maintenance



High speed cleaning machine

For full specification, installation, and maintenance details, please refer to the handbook

# Wood

## Wood

WOOD is flexible PVC decorative tile with wood design and texture produced by high pressure impact process. It benefits from PUR polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.

## Place Recommended

Housing, Healthcare, Hospital, Clinic, Office Administration, Education, Hotel, Restaurant, Retail



|  |                           |
|--|---------------------------|
|  | Size<br>152.4 x 914.4 mm. |
|  | Thickness<br>2.5 mm.      |
|  | Wear Layer<br>0.30 mm.    |
|  | Type<br>Plank             |
|  | Treatment<br>PUR          |

|        |         |        |         |        |         |            |       |            |       |
|--------|---------|--------|---------|--------|---------|------------|-------|------------|-------|
| W-2916 | Inspire | W-2913 | Inspire | TC-833 | Inspire | W-1681     | Style | W-1683     | Style |
|        |         |        |         |        |         |            |       |            |       |
| W-1819 | Style   | W-1688 | Style   | W-1623 | Style   | W-4211 NEW | Style | W-4214 NEW | Style |
|        |         |        |         |        |         |            |       |            |       |

Shades and colors may vary slightly from actual tiles, please request actual sample from Marketing and Sales Department

WOOD is flexible PVC decorative tile with wood design and texture produced by high pressure impact process. It benefits from PUR polyurethane surface treatment, making maintenance easier and eliminating the need of initial coat for light traffic area.



## EXPLODE YOUR IMAGINATION

Lot of colors, textures and surfaces are provided for supporting your dream.

## Installing

### 1. Preparing Subfloor



Hard, level, dry, smooth, sound and clean

### 2. Laying Method



2.1 Unpack tiles 24 hrs. before laying



2.2 Trace a line perpendicular to the main entrance. Ensure equal cut of tiles at the room perimeter.



2.3 Apply adhesive to a few sq.m of subfloor in one quarter



2.4 Press each tile into position



2.5 Roll with 50kg roller

## Maintenance



### Initial Cleaning



Remove loose debris



Low speed cleaning machine



### Protection



Apply wax



### Daily Maintenance



Dry sweeping or remove dirt with a damp mop



### Periodic Maintenance



High speed cleaning machine

For full specification, installation, and maintenance details, please refer to the handbook